DLA Land and Maritime - VQ Supplemental Information Sheet for Electronic QPL-3702

Specification Details: Date: 8/25/2016

Specification: MIL-DTL-3702

Title: Cable, Power, Electrical: Ignition, High-Tension

Federal Supply Class (FSC): 6145

Conventional: Yes

Specification contains quality assurance program: No MIL-STD-790 Established Reliability & High Reliability: No MIL-STD-690 Failure Rate Sampling Plans & Procedures: No

Weibull Graded: No

Specification contains space level reliability requirements: No

Specification allows test optimization: No

Contact Information:

Office of Primary Involvement: Passive Devices Branch, DLA Land and Maritime - VQP

Primary Qualifying Activity Contact: 614-692-7076, e-mail: vqp.jbc@dla.mil Secondary Qualifying Activity Contact: 614-692-2152, e-mail: vqp.cr@dla.mil

Notes:

- 1. Specification number. The type designation will consist of the defense specification number with the prefix M.
- 2. Type of shielding. The type of shielding is identified by the letter U or S as follows:
- U Unshielded
- S Shielded
- 3. Cable diameter. The cable diameter will be designated as follows:
- 5 5 millimeter (mm) nominal diameter
- 7 7 millimeter (mm) nominal diameter
- 4. Upper temperature limit. The upper temperature limit will be designated in degrees Fahrenheit (°F) as follows:
- L: Plus 250°F to minus 65 °F
- M: Plus 450°F to minus 65 °F
- H: Plus 600°F to minus 65 °F
- 5. Conductor material. The conductor material will be designated as follows:
- C Copper: 19 strands for low and medium temperature, 37 strands for high temperature
- S Steel: 7 strands, corrosion resistant
- 6. Cable applications. Cable applications will be designated as follows:
- A Air Force aircraft
- B Other than Air Force aircraft

Part Configuration:

M3702U5LSA

Prefix M	Specification	Type of	Cable	Temperature	Conductor	Cable
	Number	Shielding	Diameter	Limit	Material	Application
М	3702	U	5	L	S	Α

		PART LISTINGS	
GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
M3702-S5HCB		7622	Draka Cableteq USA, Inc.
M3702-S7HCB		7622	Draka Cableteq USA, Inc.
M3702-S5HSB		7622	Draka Cableteq USA, Inc.
M3702-S7HSB		7622	Draka Cableteq USA, Inc.
M3702-S5MCB	LSS-1853	BIW-75C012 & 7622	Draka Cableteq USA, Inc.
M3702-S7MCB	LSS-1724	BIW-73H038 & 7622	Draka Cableteq USA, Inc.
M3702-S5MSB		BIW-75C012 & 7622	Draka Cableteq USA, Inc.
M3702-S7MSB		BIW-73H038 & 7622	Draka Cableteq USA, Inc.
M3702-U5HCB		7622	Draka Cableteq USA, Inc.
M3702-U7HCB	PFWT-70	7622	Draka Cableteq USA, Inc.
M3702-U5HSB		7622	Draka Cableteq USA, Inc.
M3702-U7HSB		7622	Draka Cableteq USA, Inc.
M3702-U5MCB	LSS-1853 PRGTX-5C	BIW-75C012 & 7662	Draka Cableteq USA, Inc.
M3702-U7MCB	LSS-1724	BIW-73H038 & 7662	Draka Cableteq USA, Inc.

		PART LISTINGS	
GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	SUPPLIER'S NAME (ADDRESS ON LAST PAGE)
M3702-U5MSB		BIW-75C012 & 7622	Draka Cableteq USA, Inc.
M3702-U7MSB		BIW-73H038 & 7622	Draka Cableteg USA, Inc.

Manufacturer and Supplier Location Information

Manufacturer: Draka Cableteq USA, Inc. (CAGE Code: 71102)

Location: 22 Joseph E. Warner Boulevard, North Dighton, MA 02764-1300, US

Plants:

1. Plant: Same Address as Manufacturer